



Ficha Técnica

DESCRIPCIÓN

Temperatura de Trabajo.

- Estado estático: -40°C. a 100°C.
- Estado dinámico: -40°C. a 100°C.
- Resistencia al calor instantáneo: Hasta 120°C.

Incluye una banda interna de neopreno para un mejor sellado y sujeción.

CÓDIGO	D1	D2	L1	L2	L3	L4	B1	CABLE RANGE
	MM	MM	MM	MM	MM	MM	MM	
PG-N07	12.6	8.5	8.4	5.5	13.4	12	6.8	3.5-6
PG-N09	15.5	11	8.5	5.5	15	13.5	8.8	4-8
PG-N011	18.3	13.4	8.5	5.5	17	15	10.8	5-10
PG-N013.5	20.5	15.4	8.5	5.5	18	15	12.8	6-12
PG-N016	23	17.9	10.5	6	18.5	16.5	14.8	10,14
PG-N019	24.5	19	11	6	20	19	16	12-15
PG-N021	28.5	23	10.8	6	20.7	20	18.9	13-18
PG-N024	32.5	27	11.8	7	24.2	22	22.8	15-22
PG-N029	36.6	29	11.4	7.5	26.1	24	25.8	18-25
PG-N036	47.8	39	15	7.5	31	28	33.8	22-32
PG-N042	55	46	13.2	8	33.8	30	39	30-38
PG-N048	60	52	14.2	8	34.8	31	45	34-44
PG-N063	71.4	63.8	19.8	8.8	41.4	41.6	55	42-54